

Manuscript Number: APAC-D-16-00142R2

Title: Assessment criterion for indoor noise disturbance in the presence of low frequency sources

Article Type: Research Paper

Keywords: Noise disturbance; objective assessment method; mid-low frequency; inner comfort; measurement evaluation; noise assessment guidelines

Corresponding Author: Dr. Marco Caniato,

Corresponding Author's Institution: University of Trieste

First Author: Marco Caniato

Order of Authors: Marco Caniato; Federica Bettarello, Dr.; Chiara Schmid, prof.; Patrizio Fausti, prof.

Abstract: Several studies have presented the effects of environmental noise in and around buildings and communities in which people live and work. In particular, the noise introduced into a building is mostly evaluated using the A weighted sound pressure level (LAeq) as the only parameter to determine the perceived annoyance. Nevertheless, if noise is produced by activities or sources characterised by a low frequency contribution, the measurement of LAeq underestimates the real disturbance, in particular during sleeping time.

The international literature suggests methods to evaluate the low-frequency noise contribution to annoyance separately from the A weighted sound pressure level; almost all of the proposed methods are based on exceeding a threshold limit.

This paper tests international criteria, by applying them in real-life indoor noise situations, and then analysing, comparing and contrasting results.

Based on the result of the procedure above, a new criterion consisting of a single threshold is proposed, which simplifies the procedures in case of low-frequency components, but could be used for any situation.

## Detailed Response to Reviewers

Reviewer's comment	Authors' feedback
<p>In this article, the difference of the evaluation results by each method is mentioned. However, in this article, the number of samples for each sound sources (each one case only) is too small</p>	<p>Thank you for your suggestion.</p> <p>The number of samples for each source often was not just one measure. In fact for Large HVAC, Disco music in the same building, Live concert, Distant disco music, many measures in different days and nights were performed. What is presented in the paper is one of these measurements but the highlights we pointed out were applicable to all the measures we realized.</p> <p>Though, Authors do not think the cases number is too small, because it covers many typical disturbing sources. This paper wants to start a discussion on this topic within literature using real cases study to show and highlights the importance of this issue.</p>
<p>Regard to Live concert, Karaoke and piano bar, disco music, the sound pressure level (<math>L_{Ceq}-L_{Aeq}</math>) vary with the time variations of the sound sources. On the other hand, in regard to HVAC, the value of <math>L_{Ceq}-L_{Aeq}</math> does not vary with the time variations, this sound source is considered as a steady noise. To organize the evaluation results of each method for each sound source, the noise disturbance is present in the evaluation result of German method for only Large HVAC. In regard to /Australian methods, the noise disturbance is present in the condition of 5 kinds of sound source except for the sound of disco music coming from the same building. In addition, the noise disturbance is present for Large HVAC both the German method and the Danish/Australian methods, it is not present for the sound of disco music coming from the same building. For this reason, about the relationships between the time variations of sound sources and the evaluation result of each method, reviewer would like to investigate the influence on the evaluation results by each method of the difference of the time variations of the sound sources. Reviewer has a strong desire for the time range in the horizontal axis of Fig.1, 4-a), 6-a), 8-a), 10-a) and 12-a).</p>	<p>Thank you for your suggestion.</p> <p>The <math>L_{Ceq}-L_{Aeq}</math> difference is shown only to show how the difference between the the 1997 and the 2013 version of the DIN standard change from 20 dB to 15 dB. The clue in authors' mind was the difference between 100 ms sampling and 1 second sampling and not the time range. These two approaches provide very different results implying a misinterpretation on the final assessment as reported in paragraph 3.1 "The change of sampling clearly affects the assessment method. It is evident how the 1 second sampling hardly met the 20 dB threshold and the general sound pressure level is quite lower than the 100 ms sample one". In the standard there is no indication on the time gap usable for this comparison and so we have chosen the worst case providing the higher sound pressure level. <u>A sentence was added in the paper in paragraph 2.3.4 and in 3.1</u>  <u>The time range was added in captions as requested by reviewer</u> but authors highlight that the figures have the only aim to show the difference between the two version of the DIN and the difference of sampling methods. This latter issues, in authors' mind, is the one of paramount importance. Though the</p>

	figures do not represent the entire measures but just little samples of them, chosen in the middle of the time range where graphically the difference was clearer.
Regard to Large HVAC (Table 5) and Traditional HVAC (Table 6), the noise disturbance is present by Danish method because $L_{DA, LF}$ is greater than 20 dB in each Table 5 and 6. However, in this article, "The noise disturbance isn't present ...." is mentioned. Would you reexamine about it?	Thank you for your suggestion.  The measurements and the assessments were carried out in day time. In this period the limit of the Danish method is 25 dB and not 20 dB. <u>A specification was added in paragraphs 2.3.2 and 3.6</u>

# Assessment criterion for indoor noise disturbance in the presence of low frequency sources

## Abstract

Several studies have presented the effects of environmental noise in and around buildings and communities in which people live and work. In particular, the noise introduced into a building is mostly evaluated using the A weighted sound pressure level ( $L_{Aeq}$ ) as the only parameter to determine the perceived disturbance. Nevertheless, if noise is produced by activities or sources characterised by a low frequency contribution, the measurement of  $L_{Aeq}$  underestimates the real disturbance, in particular during sleeping time.

The international literature suggests methods to evaluate the low-frequency noise contribution to annoyance separately from the A weighted sound pressure level; almost all of the proposed methods are based on exceeding a threshold limit.

This paper tests international criteria, by applying them in real-life indoor noise situations, and then analysing, comparing and contrasting results.

Based on the result of the procedure above, a new criterion consisting of a single threshold is proposed, which simplifies the procedures in case of low-frequency components, but could be used for any situation.

## Keywords

Noise disturbance; objective assessment method; mid-low frequency; inner comfort; measurement evaluation; noise assessment guidelines;

## 1. Introduction

The existing and consolidated assessment methods of annoyance inside dwellings are widely based on the A-weighted sound pressure level measurement ( $L_{Aeq}$ ). Nevertheless this parameter leads to an underestimation of the influence of mid (generally over 250 Hz) and low (generally below 250 Hz) frequencies [1, 2, 3].

Noise disturbance has increased hugely in the last 15-20 years. Even if traffic noise is generally considered as the first cause of disturbance, both for annoyance or sleep problems, in many cases the source is related to music, people speaking or external noisy machinery. In particular, concerning the first source, weekends have become a very difficult period for inhabitants living close to venues such as clubs, discotheques and pubs. Furthermore, these activities have usually powerful external HVAC (Heating, Ventilating, Air Conditioning), increasing the noise problems at low frequencies.

Moreover, at night the residual noise is generally lower than during the daytime and consequently the disturbance is increased. In many countries, the existing regulations do not provide an objective method able to determine whether music, HVAC or other sources create annoyance in relation to a given moment or period.

Often, the criteria used are fully based on A-weighted sound pressure levels. The A-weighting is based on the peculiar perceptions of the human ear. So using  $L_{Aeq}$  level as a mean value or as the difference with background or residual noise could lead to a misinterpretation of the results, as explained below.

The background noise is defined as the  $L_{90}$  value; on the other hand the residual noise is the result of a measurement where the noise sources are turned off.

Several measurements throughout the years have shown that the A-weighted sound pressure level was misleading in determining noise disturbance. McCullough and Hetherington [4] show how this parameter underestimates the prediction of nuisance, using a in situ based measurement technique. Jakobsen [5] described how the A-weighted filter overestimates the loudness at low

54 levels at low frequencies. The authors stated that the  $L_{Aeq}$  parameter do not give a good estimate of  
55 the annoyance. Mirowska [6] as well as Cocchi et al [7] using both laboratory measurement under  
56 strict medical protocols and real case studies demonstrated how low frequencies are less tolerated  
57 and perceived as more annoying than other frequencies and then the common  $L_{Aeq}$  single number  
58 methods could not represent the a good subjective evaluation

59 Though, distorted results are possible and could depend on many reasons:

- 60 a. underestimation of structural transmissions at low frequencies,
- 61 b. time of day or night when the noise appears
- 62 c. receiver exposure time.

63  
64 As a matter of fact, if the residual noise is not characterised by low frequencies, the presence of  
65 sources with these components leads to a stronger perception [8], especially at night. Therefore it is  
66 evident that the single A-weighted sound pressure level cannot be a reliable indicator, suitable to  
67 assess whether the disturbance exists or not.

68 Because of this reason, in this paper a selected number of noise assessment criteria (both single  
69 number and frequency analysis) are tested in order to understand and compare their methods. As a  
70 result, what was found is that all these criteria do not include many issues such as precise  
71 measurements guidelines or punctual and clear measurement spot selection; furthermore they  
72 provide very different hearing or assessment thresholds. Then, a proposal for a harmonised criterion  
73 is established by combining methods supplied in the literature with those established by the Italian  
74 legislation.

75 The proposed method is to be used in lawsuits, disputes or whenever an objective evaluation is  
76 needed. In this study, noise disturbance is considered both as annoyance and sleep disturbance.

## 77 2. Literature review

### 78 2.1 General studies and soundscape approach

79 In the last decades many authors have described the sound pressure level risks [9] both outside  
80 and inside dwellings. Miedema and Oudshoorn [10] connected annoyance with noise, focusing on  
81 transportation noise using DNL and DEN values. Even if this is a very good method, it requires  
82 very long measurements and only works for transportation sources. Indeed, it is difficult to apply it  
83 to disco pubs, people speaking, HVAC, etc.

84 More recently, the COST TUD action TD 0804 collected a large number of results obtained by  
85 different participants worldwide. Within the published e-book [11], many issues are presented in  
86 order to investigate noise and soundscape. The definition of soundscape, using the standard ISO  
87 12913-1:2014 [12], is as follows: “acoustic environment as perceived or experienced and/or  
88 understood by a person or people, in context”.

89 In particular, Kang et al. [11] report that over 30 % of the EU population is exposed to noise  
90 levels above the WHO recommendation; Drever [13] studied the effect of ultra-rapid “ecological”  
91 hand dryer on vulnerable groups; Ortiz et al. [14] focused on quiet zones; Lercher et al. [15] studied  
92 the noise effects on children; Prodi et al [16] studied the impact of noise on intelligibility in  
93 classrooms; Hiramatsu [17] connected noise and soundscape. These studies were very important in  
94 order to understand the subjective effect on receivers, but it does not supply an objective method to  
95 assess the disturbance.

96 Soundscape studies approach noise as a “resource” rather than “waste” [9]. In lawsuits or  
97 disputes, however, this approach is never used. In addition, it requires people to complete  
98 questionnaires regarding their positive or negative feelings towards sounds and noise. In a dispute,  
99 these results become difficult to use, as the different parties are not interested in soundscapes, but  
100 rather in winning the case.

101 None of these methods takes into account the façade, airborne and impact sound insulation in  
102 buildings because disturbance is measured in the context in which it takes places (noise  
103 propagation, time of day and night, etc). Therefore, in order to evaluate the annoyance of the  
104 intruding noise, its characteristics are more important than the way in which it enters the dwelling.

107 Clearly, the sound insulation performance of the building can affect the final perception of the  
108 intruding noise [18], even at low frequencies or in the case of impact noise [19, 20]. Nevertheless,  
109 this relates only to the rating of the buildings [21, 22] and not to the evaluation of the intruding  
110 noise. In order to reduce disturbance, when necessary, sound insulation can be improved or the  
111 noise level of the source can be reduced.

## 114 **2.2 Single value: $L_{Aeq}$ based techniques**

### 116 **2.2.1 International method: WHO guidelines**

117 The WHO guidelines [23] are frequently used in the acoustical community. They propose  
118 health-based limits for night noise exposure stating that noise nuisance exists when the measured  
119  $L_{Aeq}$  value inside a dwelling at night exceeds 30 dB(A), with higher limits when short-term  
120 measurements or maximum values are considered. Furthermore, it is specified that an external level  
121 below 30 dB(A) does not create negative effects on the health of the dwellers, including vulnerable  
122 groups such as children. This limit is to be considered as a long-period equivalent level. Interim  
123 levels of 40 dB(A) and 55 dB(A) were also proposed where the 30 dB(A) ultimate target cannot be  
124 achieved in a short period.

125 The WHO approach sets maximum thresholds for both inner and outer levels. Noise levels  
126 exceeding these thresholds are deemed to disrupt sleep. It was mainly created for traffic noise and it  
127 is based on overall levels ( $L_{Amax}$  and  $L_{Aeq}$ ) only. This makes measurements and post-elaboration  
128 fairly easy, but does not take into account the mid-low frequencies contribution. The use of a single  
129 number value could lead to an underestimation of the noise disturbance since it is the average of  
130 every frequency from 20 Hz to 20000 Hz. Then it could take into account different sources from the  
131 studied one(s) and (because it is weighted) it modifies the frequency and though the final  
132 evaluation.

### 134 **2.2.2 Regional methods: Italian methods**

135 As an example, Italian methods are presented, the first is required by the applicable legislation  
136 [24] and the second is an agreed but not codified “comparative” system adopted when the actual  
137 conditions do not allow the use of the mandatory method. It is sometimes used in court if required  
138 by the judge.

139 The first method consists of the  $L_{Aeq}$  measurement and third octave bands analysis with a  
140 minimum sampling rate of 125 ms. This is necessary for the investigation of tonal or impulsive  
141 events in the measured signal (frequency range 20 Hz – 20000 Hz).

142 The final values need to comply with the mandatory requirements specifying separate limits for  
143 daytime and night time. These limits take into account both external and internal acoustic  
144 conditions. The outer (*absolute*) values are not to be exceeded and are based on equivalent levels  
145 over the whole day or night periods. The inner values (*differential*) are evaluated considering the  
146 difference between the environmental and the residual noise (noise source switched off). If the  
147 measured  $L_{Aeq}$  is greater than the residual noise by 5 dB during the day (6-22) and 3 dB during the  
148 night (22-6), then the measured noise is regarded as disturbance. The measurements are based on  
149 short-term periods (about 1 to 20 minutes for example), with the disturbing source on and off.

150 There are lower minimum limits for the applicability of this method: the disturbing noise has to  
151 be greater than 50 dB(A) during daytime and 40 dB(A) during night time within the dwelling with  
152 open windows and 35 dB(A) and 25 dB(A) within the dwelling with closed windows. The  
153 differential limits do not apply to any type of traffic sources.

154 The mid-low frequency effect is taken into account only for tonal phenomena (a noise in which  
155 a frequency is predominant) but not for broadband. The very high sampling definition requires the  
156 acquisition of a lot of data. As a consequence, measurements and post processing are difficult, and  
157 expensive sound level meters are needed.

158 The “comparative method”, is sometime used in lawsuits, but it has no scientific bases. As a  
159 consequence no robust results are supplied.

## 2.3 Frequency analysis based methods

### 2.3.1 Polish criterion

The Polish criterion is robust and detailed [6] and its use was made a legal requirement (see for application chapter 3). It establishes two control conditions for the definition of indoor noise disturbance: the 1/3 octave band  $L_{eq}$  spectrum needs to exceed the given threshold and the measured value needs to exceed the background noise by 6 dB. Background noise is defined as the noise measured when no disturbing and thus measurable source is active (i.e. residual noise). The noise constitutes a nuisance if both of the above conditions are met in any 1/3 octave band between 10 Hz and 250 Hz. No measurement guidelines are given and no sampling criterion is included.

This method is based on both clinical and acoustical evidence and it is the only method taking into account residual noise and considering a wide frequency range (up to 250 Hz).

### 2.3.2 Danish criterion

This method [5] focuses on the 10 Hz – 160 Hz bandwidth and uses a logarithmic summation of these 1/3 octave bands but no sampling criterion is included. Its application is required by the law. The obtained value, named  $L_{pA,LF}$ , must not be greater than  $L_{pA,LF} = 25$  dB during day time and  $L_{pA,LF} = 20$  dB during night time inside dwellings. A maximum value of  $L_{pG} = 85$  dB(G) (using G-weighting) is required for infrasound, splitting the low frequency domain.

The measurements must be performed in three different positions and the final value is obtained by averaging the measurements. This method combines measuring guidelines and an assessment of vibration and refers to the background noise measured when the noise source is turned off (residual noise).

### 2.3.3 Australian criterion (I)

This method [25] is almost equal to the Danish method, but the limit is reduced by 5 dB in the event that the source is disco music.

### 2.3.4 German criterion

This is the only standardised method within DIN 45680:1997 [26]. This German standard was reviewed in 2011 and 2013 [27] and two unapproved drafts are currently being discussed.

A first check is made on the measured noise: if  $L_{Ceq}$  is 20 dB (15 dB in the 2011 and 2013 drafts) higher than  $L_{Aeq}$ , then the disturbance can be evaluated. No time range is indicated as reference period. To do so, the exposition period and the rating time must be assessed; no sampling criterion is included. The residual noise must be 6 dB below the disturbing noise. The standard requires measurement with linear weighting.

Once the above steps have been completed, the linear  $L_{eq}$  is weighted with high penalising  $k_{ai}$  coefficients derived from the EN 60651 standard [28]. The final value is compared with daytime, evening and night time limits. Then, a logarithmic summation of 8 Hz to 100 Hz 1/3 octave bands is required, but only for those that are higher than the threshold indicated for the disturbance. The 2011 and 2013 DIN 45680 drafts use the ISO 226 [29] threshold, while the DIN 45680:1997 version is based on the threshold provided by the same standard.

## 2.4 External noise criterion

This criterion is used in the Australian method II [30]. According to this system, the noise is measured outside the building using a C weighting curve. The measurement procedure is simple (no need to access the dwellings by night, no need to arrange measurement time and day etc.).

Nevertheless, neither the noise source within the same receiver building nor structural transmission (through substructures etc.) are taken into account.

Other methods using only external noise exist, but they contain almost the same issues of the presented one.



213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65

### 3. Application in real-life cases

In recent years, several measurements were carried out by the authors with different types of sources and different situations for the receiver.

For discotheques, pubs etc. the noise disturbance can be divided in two categories:

- 1) People speaking outside;
- 2) Music source from live concerts, disc-jockeys, karaoke, HVAC etc.

The first case has already been discussed in [31] and other similar cases where presented in [32], with both environmental health officers and researchers/engineers arriving to the same conclusions while using different methods. In the second case, different assessment methods lead to different results.

In the following paragraphs, the results of the application of different methods for any of the different types of sources, are shown. In the following figures, the general definition of “level (dB)” reported in y axes, refers to what the specific paragraph is concerning about.

#### 3.1 Live concerts

In the following example, the indoor noise disturbance in a residential apartment came from the live concert inside a music pub (blues/jazz/pop music). The disturbed room was located on the second floor of the building and the pub was located on ground floor of the same building.

##### - German criterion

The first step is to verify the 20 dB (or 15 in the drafts) threshold between  $L_{Ceq}$  and  $L_{Aeq}$ . Figure 1 shows the comparison between 100 ms sampling and 1 second sampling rate. In the standard there is no indication on the time gap usable for this comparison and so it was chosen the worst case providing the higher sound pressure level. The change of sampling clearly affects the assessment method. It is evident how the 1 second sampling hardly met the 20 dB threshold and the general sound pressure level is quite lower than the 100 ms sample one. Furthermore, the 20 dB threshold is very difficult to reach. No indication is given of whether a single excess in an individual sample is enough to move on to the next steps, or whether the whole measurement has to exceed the threshold to continue the assessment.

The second step provides a comparison between the 1/3 A weighted octave bands ( $L_{terz,r}$ ) and the DIN 45680 threshold (figure 2).




Figure 1 – Operability threshold (20 dB yellow line, 15 dB green line) according to DIN 45680 (time range 22.15 – 23.37).



1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65




Figure 2 – comparison between the 1/3 A weighted octave bands ( $L_{terz,r}$ ) and the DIN 45680 threshold

In this case, the 80 Hz and 100 Hz bands exceed the limit. Using the corrections of  $k_{ai}$  coefficients provided in Annex 1 of the DIN 45680, the obtained overall value of the noise inside the room is 18.9 dB(A). According to the night time limits provided (25 dB(A)), no disturbance is found.

- Polish method

Figure 3 (a) shows a comparison between the noise level  $L_{Aeq}$  and A weighted background noise; the threshold curve  $L_{A10}$  is also reported. Figure 3 (b) shows the difference between  $L_{Aeq}$  and the threshold values ( $\Delta L_1$ ) and between  $L_{Aeq}$  and background level ( $\Delta L_2$ ). In the first case the disturbance is verified for  $\Delta L_1 > 0$ ; in the second one the disturbance is verified for  $\Delta L_2 > 6$  dB.




Figure 3 – Polish method trends, (a) noise and threshold; (b) defined parameters

The presence of disturbance between 80 Hz and 250 Hz is evident, as it is when applying the German method (before  $k_{ai}$  weighting).

- Danish method

Here the comparison between A-weighted sound pressure level for low frequencies ( $L_{pA,LF}$ ) within 1/3 octave bands 10 Hz to 160 Hz range and G-weighted for infrasound ( $L_{pG}$ ) and given daytime and night time limits is reported. For the latter period these are  $L_{pA,LF} = 20$  dB(A) maximum and  $L_{pG} = 85$  dB(G) maximum. Table 1 shows the final measured values.

Table 1– noise trends  $L_{pA,LF}$  and  $L_{pG}$  parameters

Frequency [Hz]	$L_{pA,LF}$ (dB(A))	$L_{pG}$ (dB(G))
10.0	-36.2	34.2
12.5	-34.2	33.2

16.0	-30.4	34.0
20.0	-28.6	30.9
25.0	-16.5	31.9
31.5	-6.4	29.0
40.0	-1.4	21.2
50.0	7.5	17.7
63.0	8.3	6.5
80.0	18.2	4.7
100.0	20.8	-4.1
125.0	23.4	-12.5
160.0	27.9	-18.7
overall	30.2	40.4

The noise disturbance is present at low frequencies but not in the infrasound range.

- *Australian method (I)*

This method is very similar to the Danish method, but for impulsive sources like disco music the given limit is 5 dB(A) lower. This penalisation has not been applied in the case analysed here (live music). Noise assessment with the Australian method produced exactly the same results as with the Danish method.

**3.2 Karaoke and piano bar**

In this case the measurements were carried out inside a dwelling during a piano bar and karaoke night; the disturbance came from both inside and outside the pub.

- *German method*

Figure 4 shows the difference between  $L_{Ceq}$  and  $L_{Aeq}$  represented with 100 ms sampling; both thresholds (15 and 20 dB(A)) are exceeded. The comparison between the 1/3 A weighted octave bands ( $L_{terz,r}$ ) and the DIN 45680 threshold is then provided.




Figure 4 – (a) first step (time range 22.06 – 23.01) and (b) 1/3 octave band assessment

The noise disturbance is found from 80 Hz. Nevertheless, if  $k_{ai}$ -weighting is applied the final value is 16.2 dB(A). Since the night limit is 25 dB(A), no disturbance can be ascertained.

- *Polish method*

Figure 5 shows a comparison between the noise level  $L_{Aeq}$  and residual noise and the difference between  $L_{Aeq}$  and the threshold values ( $\Delta L_1$ ) and between  $L_{Aeq}$  and residual level ( $\Delta L_2$ ). This method shows a wider noise disturbance range (from 80 Hz to 250 Hz).




Figure 5 – Polish method trends, (a) noise and threshold; (b) defined parameters

- Danish method

Here for the night time period these are  $L_{pA,LF} = 33.9$  dB(A) maximum and  $L_{pG} = 58$  dB(G) maximum. Table 2 shows the final measured values.

Table 2– noise trends  $L_{pA,LF}$  and  $L_{pG}$  parameters

Frequency [Hz]	$L_{pA,LF}$ (dB(A))	$L_{pG}$ (dB(G))
10.0	-13.4	57.0
12.5	-19.4	48.0
16.0	-18.7	45.7
20.0	-14.7	44.8
25.0	-18.4	30.0
31.5	-10.5	24.9
40.0	0.2	22.8
50.0	-2.1	8.1
63.0	7.7	5.9
80.0	27.1	13.6
100.0	29.7	4.8
125.0	22.3	-13.6
160.0	29.1	-17.5
overall	33.9	58.0

The noise disturbance is present at low frequencies but not in the infrasound range.

- Australian method (I)


This method is very similar to the Danish method, but for impulsive sources like disco music the given limit is 5 dB(A) lower. This penalisation has not been applied in the case analysed here (live music). Noise assessment with the Australian method produced exactly the same results as with the Danish method.

**3.3 Distant disco music**

Here, the indoor noise disturbance comes from a club 70 meters away . The sources are both disco music and a live concert, often playing with open windows and doors.

- German method

322 Figure 6 shows the difference between  $L_{Ceq}$  and  $L_{Aeq}$  represented with 100 ms sampling; both  
 323 thresholds (15 and 20 dB(A)) are exceeded. The comparison between the 1/3 A weighted octave  
 324 bands ( $L_{terz,r}$ ) and the DIN 45680 threshold is then provided.  
 325  
 326  
 327




18 Figure 6 – (a) first step (time range 23.45 – 00.15) and (b) 1/3 octave band assessment

209 The noise disturbance is found from 100 Hz. This is due to the absence of structural  
 210 transmissions. Nevertheless, applying the  $k_{ai}$ -weighting, the final value is 16.2 dB(A). Since the  
 211 night limit is 25 dB(A), no disturbance is confirmed.  
 212

213 - Polish method

214 Figure 7 shows a comparison between the noise level  $L_{Aeq}$  and residual noise and the difference  
 215 between  $L_{Aeq}$  and the threshold values ( $\Delta L_1$ ) and between  $L_{Aeq}$  and residual level ( $\Delta L_2$ ). This method  
 216 evidences a noise disturbance range from 100 Hz.  
 217



31 Figure 7 – Polish method trends, (a) noise and threshold; (b) defined parameters

32 - Danish method

33 Here for the night time period these are  $L_{pA,LF} = 24.9$  dB(A) maximum and  $L_{pG} = 45.3$  dB(G)  
 34 maximum. Table 3 shows the final measured values.  
 35

36 Table 3– noise trends  $L_{pA,LF}$  and  $L_{pG}$  parameters

Frequency [Hz]	$L_{pA,LF}$ (dB(A))	$L_{pG}$ (dB(G))
10.0	-26.2	44.2
12.5	-29.9	37.5
16.0	-33.2	31.2
20.0	-35.7	23.8
25.0	-32.0	16.4
31.5	-16.9	18.5

40.0	-7.3	15.3
50.0	6.3	16.5
63.0	9.9	8.1
80.0	1.1	-12.4
100.0	14.2	-10.7
125.0	22.8	-13.1
160.0	18.8	-27.8
overall	24.9	45.3

The noise disturbance is present at low frequencies but not in the infrasound range.

- *Australian method (I)*

This method is very similar to the Danish method, but for impulsive sources like disco music the given limit is 5 dB(A) lower. This penalisation has not been applied in the case analysed here (live music). Noise assessment with the Australian method produced exactly the same results as with the Danish method.

**3.4 Disco music coming from the same building**

The measurements were carried out inside a block of flats, in the apartment belonging to a family who complained about the noise from a disco club.

- *German method*

Figure 8 shows the difference between  $L_{Ceq}$  and  $L_{Aeq}$  represented with 100 ms sampling; both thresholds (15 and 20 dB(A)) are exceeded. The comparison between the 1/3 A weighted octave bands ( $L_{terz,r}$ ) and the DIN 45680 threshold is then provided.




Figure 8 – (a) first step (time range 01.38 – 02.15) and (b) 1/3 octave band assessment

The noise disturbance is found from 50 Hz, highlighting the structural path as predominant. Nevertheless, applying the  $k_{ai}$ -weighting, the final value is 24.4 dB(A). Since the night limit is 25 dB(A), no disturbance is confirmed.

- *Polish method*

In figure 9 a comparison between the noise level  $L_{Aeq}$  and residual noise and the difference between  $L_{Aeq}$  and the threshold values ( $\Delta L_1$ ) and between  $L_{Aeq}$  and residual level ( $\Delta L_2$ ) is shown. This method evidences a noise disturbance range from 80 Hz.




Figure 9 – Polish method trends, (a) noise and threshold; (b) defined parameters

- Danish method

Here for the night time period these are  $L_{pA,LF} = 19.5$  dB(A) maximum and  $L_{pG} = 57.8$  dB(G) maximum. Table 4 shows the final measured values.

Table 4– noise trends  $L_{pA,LF}$  and  $L_{pG}$  parameters

Frequency [Hz]	$L_{pA,LF}$ (dB(A))	$L_{pG}$ (dB(G))
10.0	-13.4	57.0
12.5	-19.4	48.0
16.0	-18.7	45.7
20.0	-23.4	36.1
25.0	-22.9	25.5
31.5	-12.9	22.5
40.0	-6.9	15.7
50.0	4.5	15.2
63.0	8.4	7.6
80.0	9.4	-4.1
100.0	14.3	-10.6
125.0	12.6	-20.3
160.0	14.1	-32.0
overall	19.5	57.8

The noise disturbance is not present at low frequencies as well as in the infrasound range.

- Australian method (I)

This method is very similar to the Danish method, but for impulsive sources like disco music the given limit is 5 dB(A) lower. This penalisation was applied in the case analysed here (Disco music) and so the disturbance was assessed.

**3.5 Large HVAC**

In this case, the noise came from a large (4x2x2 meters) HVAC system for winter and summer air and water conditioning unit located at a distance of 1 meter from the receiver windows. It had in-built silencers and noise barriers. The measurements were carried out during daytime.

- German method

Figure 10 shows the difference between  $L_{Ceq}$  and  $L_{Aeq}$  acquired with a 100 ms sampling rate, where only the 20 dB(A) threshold is exceeded. The comparison between the 1/3 A weighted octave bands ( $L_{terz,r}$ ) and the DIN 45680 threshold is then provided.




Figure 10 – (a) first step (time range 17.30 – 18.30) and (b) 1/3 octave band assessment

The disturbance cannot be assessed as the  $L_{Aeq} - L_{Ceq}$  check never exceeds 15 dB. Nevertheless, if the standard method is used, the output values exceed the threshold starting from 50 Hz and by applying the  $k_{ai}$ -weighting the final value is 29.5 dB(A), which confirms the disturbance.

- Polish method

Figure 11 shows a comparison between the noise level  $L_{Aeq}$  and residual noise and the difference between  $L_{Aeq}$  and the threshold values ( $\Delta L_1$ ) and between  $L_{Aeq}$  and residual level ( $\Delta L_2$ ). This confirms a disturbance at 50 Hz and from 100 Hz.




Figure 11 – Polish method trends, (a) noise and threshold; (b) defined parameters

- Danish method

Here for the night time period these are  $L_{pA,LF} = 24.6$  dB(A) maximum and  $L_{pG} = 51.3$  dB(G) maximum. Table 5 shows the final measured values.

Table 5– noise trends  $L_{pA,LF}$  and  $L_{pG}$  parameters

Frequency [Hz]	$L_{pA,LF}$ (dB(A))	$L_{pG}$ (dB(G))
10.0	-42.0	28.4
12.5	-34.5	32.9
16.0	-15.6	48.8
20.0	-14.8	44.7
25.0	-5.4	43.0
31.5	1.0	36.4
40.0	4.1	26.7
50.0	19.1	31.1
63.0	6.6	4.8
80.0	6.0	-7.5
100.0	12.8	-11.1



125.0	17.2	-17.7
160.0	20.9	-20.7
overall	24.6	51.3

The noise disturbance isn't present at both at low frequencies and in the infrasound range.

- *Australian method (I)*

This method is very similar to the Danish method, but for impulsive sources like disco music the given limit is 5 dB(A) lower. This penalisation has not been applied in the case analysed here (HVAC). Noise assessment with the Australian method produced exactly the same results as with the Danish method.

**3.6 Traditional HVAC**

The measurements are carried out inside an apartment located on the 4<sup>th</sup> floor of a building; the indoor noise disturbance comes from a traditional (air cooling 1x0.8x0.4 m) HVAC system located in the courtyard. The measurements were carried out during daytime

- *German method*

Figure 12 shows the difference between  $L_{Ceq}$  and  $L_{Aeq}$  acquired with a 100 ms sampling rate; both thresholds (15 and 20 dB(A)) are exceeded. The comparison between the 1/3 A weighted octave bands ( $L_{terz,r}$ ) and DIN 45680 threshold is then provided.





Figure 12 – (a) first step (time range: 20.30 – 22.00) and (b) 1/3 octave band assessment

The noise disturbance is found starting from 50 Hz. Nevertheless, if the  $k_{ai}$ -weighting is applied, the final value is 16.4 dB(A). Since the night limit is 25 dB(A), no disturbance is ascertained.

- *Polish method*

Figure 13 shows a comparison between the noise level  $L_{Aeq}$  and residual noise and the difference between  $L_{Aeq}$  and the threshold values ( $\Delta L_1$ ) and between  $L_{Aeq}$  and residual level ( $\Delta L_2$ ). No disturbance is ascertained.



1  
2  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
432  
433  
434  
435  
436  
437  
438  
439  
440  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65

Figure 13 – Polish method trends, (a) noise and threshold; (b) defined parameters

- Danish method

Here for the night time period these are  $L_{pA,LF} = 23.0$  dB(A) maximum and  $L_{pG} = 59.3$  dB(G) maximum. Table 6 shows the final measured values.

Table 6– noise trends  $L_{pA,LF}$  and  $L_{pG}$  parameters

Frequency [Hz]	$L_{pA,LF}$ (dB(A))	$L_{pG}$ (dB(G))
10.0	-14.5	55.9
12.5	-11.7	55.7
16.0	-17.1	47.3
20.0	-14.8	44.7
25.0	-10.1	38.3
31.5	-5.9	29.5
40.0	4.4	27.0
50.0	18.9	29.1
63.0	11.8	10.0
80.0	14.1	0.6
100.0	8.7	-16.2
125.0	11.9	-24.0
160.0	17.2	-29.4
overall	23.0	59.3

The noise disturbance isn't present at both at low frequencies and in the infrasound range.

- Australian method (I)

This method is very similar to the Danish method, but for impulsive sources like disco music the given limit is 5 dB(A) lower. This penalisation has not been applied in the case analysed here (HVAC). Noise assessment with the Australian method produced exactly the same results as with the Danish method.

**3.7 Discussions of results**

All methods require the 1/3 octave band frequency analyses and provide specifications on background noise conditions. Some of them contain measurement specifications and only one introduces a penalty depending on the disturbance occurring by day or by night.

The German method does not confirm the existence of the disturbance at any time while the Danish/Australian methods, in most cases, do. No method considers the frequency trend of the source, nor the influence of multiple sources, nor the sampling measurement step.

Some processes require multiple measurements and supply hearing or disturbance thresholds. Finally, the different frequency ranges are investigated and no importance is attached to the windows being open or closed.

If the measure is slightly over the threshold changing receiver positions, sampling, etc. can affect the final result regardless of the chosen method.

If no strict rules are imposed on the measurement and parameters methodology, the results cannot be compared and disturbance cannot be clearly and objectively assessed.

**4. Proposal for a harmonised assessment criterion**

Since measuring subjective disturbance is impossible as each individual has is sensitive to noise in a different way, no universal threshold can and will ever be established. Despite the use of

475 subjective interviews for example in soundscapes [11], in the cases described here the noise is  
 476 considered a disturbing source and never a positive contribution. Subjective evaluations,  
 477 particularly in the case of legal disputes, are not a reliable form of measurement.

478 Nevertheless, several studies have been carried out over the years in many different countries  
 479 using laboratory subjective tests in order to obtain a hearing/disturbance threshold [2,3,5,6,11].  
 480 Determining a new threshold using subjective tests therefore makes little sense.

481 The aim of this work is to determine an objective method to assess the noise disturbance  
 482 (considered both as annoyance and sleep disturbance) in the usual conditions and for the average  
 483 individual, taken for granted that this is the only way to include as many people as possible. So it  
 484 makes sense to calculate the average of the hearing thresholds included in standards/literature as  
 485 presented in figure 14 and table 7, since they come from different authors who have used different  
 486 techniques and operate in different part of the world and since these thresholds are average  
 487 themselves. In a way, this represents the “average of the averages”.




Figure 14 – literature standard and average of the averages trends

Hz	dB
8	100.2
10	90.9
12.5	83.3
16	76.9
20	72.7
25	64.5
31.5	57.3
40	51.1
50	45.9
63	42.6
80	38.7
100	36.2
125	35.2
160	31.5
200	28.5
250	21.5

Table 7 – average of the averages

489 After all this case history, the present study suggests the following steps in order to assess  
 490 disturbance:

- 491 1) Noise should be measured both inside the dwelling where the disturbance is higher and at  
 492 the source. If the source signal is stable enough, then this measurement can be carried out  
 493 separately. If the 1/3 octave bands trend of the former is comparable with the latter (also a  
 494 composition of frequencies due to many sources), then this method can be used, according to  
 495 [7].

496 The source(s) measurements have to be carried out at a distance of 1 meter from the highest  
 497 emitting point. If the noise source is composite (industrial plant) then the receiver should be  
 498 placed in a spot equally distant from the different sources in a normal direction starting from  
 499 the focal point of the overall surface. If this is not possible (close walls, irregular shape) the  
 500 instrument needs to be placed closer to the surface, remaining in a normal direction starting  
 501 from the focal point.

- 502 2) The residual noise (source(s) off) should be measured in the same period of the day and  
 503 week before or after the noise source is used.

- 3) The residual noise should be compared and contrasted with the disturbing noise. If the difference (in 1/3 octave band analysis) is higher than 6 dB according to [6], the disturbance can be evaluated using following steps.
- 4) The measured disturbing noise within the dwellings should be compared and contrasted with the average threshold. If the former exceeds the latter two different scenarios must be considered:
  - a. If it is night time (from 22 to 7 h); if the receivers are children up to the age of 3 or people with serious illnesses (all day long); if the receivers are in hospitals or schools or buildings where silence is needed (all day long), then the excess of the threshold confirms the existence of the disturbance. Night time period (22-7) represents the typical and average sleeping time of children and workers.
  - b. If none of the above conditions applies, the excess has to be equal to or higher than 3 dB according to [23] in any 1/3 octave band.

Measurement guidelines:

- 1) A minimum of three different 15-minute measurements are to be averaged. If the noise is shorter, then the use of multiple receivers is needed (3 minimum) with at least 1 minute measurement time each. The microphone(s) need to be 50 cm away from each other. If the noise source(s) is not constant (e.g. concert, short and repeated HVAC cycle etc.) and the related residual noise is shorter than 2 minutes, then the measures have to be post-processed in order to compute the disturbing noise only and exclude the residual noise. The minimum sampling step is set to 1 second, based on authors experience realizing this study. The described time ranges are based on the authors' measurement experience related to the development of this study and concern the minimum time lapse within whom the sound event could be considered robust and reliable.
- 2) At the same time an instrument must be placed near the source(s) in order to acquire the frequency trend. If the signal is stable enough, then this measurement can be carried out separately (before or after those in the dwelling).
- 3) No other person except the engineer(s) must be present during the measurements. All the external acoustic events are to be taken into account and post-processed to avoid any outer interference.
- 4) All doors and windows must be closed.
- 5) The measurements must be carried out in closed rooms such as dining room, living room, bedroom, etc. No corridors, storerooms, bathrooms smaller than 8 square meters (minimum area for repeatable measurements, taking into account furniture, room shape etc.) should be considered.

When providing results:

- 1) Report measurement methodology
- 2) Identify irrelevant acoustic events during occurring during measurement operation and do not factor them in while assessing the disturbance
- 3) Report name, type and certification of the instrumentation
- 4) Describe the source type and report the frequency and trend.
- 5) Attach pictures of the measurements and of the sources
- 6) Report the 1/3 octave band assessment trend and indicate if and where the presence of a noise disturbance is confirmed
- 7) Propose possible solutions

**5. New method application**

The 6 cases discussed above were used to test, analyse and assess the methods proposed in the literature, to understand their rationale and identify potential issues. Lessons were in this way learned and translated into a new method meant to provide an objective assessment of noise

559 disturbance, which was obviously not available when the 6 cases above were initially assessed and  
560 could therefore not be applied.

561 Following its creation, chances arose to apply the new method in just two of the six above  
562 discussed:


- 563 1) Disco music coming from the same building (paragraph 3.4). Here the noise was measured  
564 by night and no receivers listed in 4) sub a) with no receivers as described in point 4) sub a)  
565 in the building
- 566 2) Large HVAC (paragraph 3.5). Here the noise was measured by night and no receivers listed  
567 in 4) sub a) with no receivers as described in point 4) sub a) in the building  
568

569  
570 The comparison with the described literature methods could not be reported since the new  
571 criterion obtained results could not be compared with other results. This fact is caused by the  
572 different measurement guidelines approach (sampling, time rate, frequency range, thresholds,  
573 weighting, and measurements number). So final results would be sensibly affected by these  
574 differences.

575 In 1) the methods provided in the literature produced very diverging results. Those who dwelt  
576 inside the building while the measures were in progress nevertheless unanimously reported the  
577 presence of a noise disturbance (first step, fig. 15). The proposed approach also confirmed the  
578 existence of the disturbance. The source was subsequently modified (by means of a limiter and a  
579 DSP analyser) and the disturbance was measured by 2 different teams. The new method was used in  
580 addition to the old method in order to contrast results.

581 By using the methods proposed in the literature, the 2 teams once again obtained diverging  
582 results, owing to unspecific measurement procedures and uncertainty as to which threshold should  
583 be applied in which case.

584 By using the new method, the 2 teams obtained comparable results and concluded that there was  
585 no disturbance (second step, fig. 15), which was in line with the subjective perception of the police,  
586 present in the building, and the owners of the building  
587



588  
589 Figure 15 – the new method applied in real-life circumstances (see paragraph 3.4)  
590

591 In 2), the results obtained using the methods provided in the literature are at utter variance,  
592 although all those who dwelt inside the building while the measures were in progress agreed that the  
593 disturbance was there (first step, fig. 16). The disturbance could also be identified using the new  
594 method. The source was then modified by applying the appropriate silencer and the new method  
595 was used along the old method to assess the disturbance, so that the results could be contrasted.

60  
61  
62  
63  
64  
65

596 And again, using the methods proposed in the literature, the team obtained diverging results,  
597 owing to unspecific measurement procedures and uncertainty as to which threshold should be  
598 applied in which case

599 By using the new method, the team concluded that there was no disturbance (second step, fig.  
600 16), which was in line with the subjective perception of the police, present in the building, and the  
601 owners of the building  
602




Figure 16 -- the new method applied in real-life circumstances (see paragraph 3.5)

## 6. Conclusions

Sound measurements inside dwellings are commonly used to understand noise and sleep disturbance. As a consequence, many researchers worldwide have tried to determine objective methods to assess whether a disturbance is present or not. Some countries use the discussed criteria and have made their use compulsory. Each method focuses on some features, leaving possible interpretations to the engineers, which may cause misunderstandings. The goal of this paper is to inform stakeholders in the drafting of new standards or legislation, or in the integration of existing legal requirements by proposing an objective method built on robust and scientific criteria that should replace the current, unreliable but widely used procedures and their subjective interpretation.

To this end, an in-depth analysis of different disturbance assessment methods was carried out. Six different traditional sources were analysed and measured and results were compared and contrasted. Pros and cons were highlighted and a new assessment criterion was proposed and successfully tested combining, where possible, the different approaches and standards discussed in the literature. A new average threshold is supplied which simplifies the procedures in case of low-frequency components, but which could be used for any situation. This is complemented with new and well defined measurement steps and guidelines.

### Acknowledgments

Many thanks to Andrea Tombolato who inspired this work and to Andrea Caniato for consultation on the German standards. This research was funded with a Ph.D scholarship by MIUR (Italian Ministry of University) which is gratefully acknowledged.

### Author Contributions

All the authors contributed equally to the conception of this study



632 **7. References**

- 633
- 634 [1] Persson, K., Björkman, M., And Rylander, R., *Loudness, Annoyance and dBA in Evaluating*
- 635 *Low Frequency Sounds*, Journal of Low Frequency Noise And Vibration, Vol. 9, No. 1, 1990
- 636 [2] Vercammen M.L.S., *Low-frequency noise limits*, Journal of low frequency noise and
- 637 vibrations, **11** (1992), pp. 7-13
- 638 [3] Vercammen M.L.S., *Setting limits for low frequency noise*, Journal of low frequency noise
- 639 and vibrations, **8** (1989), pp. 105-108
- 640 [4] McCullough P., Hetherington J. O., *A Practical Evaluation of Objective Noise Criteria used*
- 641 *for the Assessment of Disturbance due to Entertainment Music*, Journal of Environmental
- 642 Health Research, **4** (2005), pp. 69-74
- 643 [5] Jakobsen, J., *Danish Guidelines on Environmental Low Frequency Noise, Infrasound and*
- 644 *Vibration*, Journal of Low Frequency Noise, Vibration And Active Control, Vol. 20, No. 3
- 645 (2001), pp 141-148
- 646 [6] Mirowska M.J., *Evaluation of low-frequency noise in dwellings. New Polish*
- 647 *Recommendations*, Journal of Low Frequency Noise, Vibration And Active Control, Vol. 20,
- 648 No. 2 (2001), pp 69-74
- 649 [7] Cocchi A., Fausti P., Piva S., *Experimental characterisation on the low frequency noise*
- 650 *annoyance arising from industrial plants*, Journal of low frequency noise and vibration,
- 651 vol.11, No. 4, (1992), pp. 124-132
- 652 [8] Drexl M., Otto L., Wiegrebe L., Marquardt T., Gürkov R., Krause E., *Low-frequency sound*
- 653 *exposure causes reversible long-term changes of cochlear transfer characteristics*, Hearing
- 654 Research, Volume 332, February 01, 2016, Pages 87-94
- 655 [9] Babisch W., *The noise/stress concept, risk assessment and research needs*, Noise Health
- 656 2002;4:1-11
- 657 [10] Miedema H.M.E., Oudshoorn C.G.M., 2001, *Annoyance from transportation noise:*
- 658 *relationships with exposure metrics DNL and DENL and their confidence intervals*. Environ.
- 659 Health Perspect. 109, 4 (April)
- 660 [11] Kang J., Chourmouziadou K., Sakantamis K., Wang B., Hao Y. (edited by), *Soundscape of*
- 661 *European Cities and Landscape*, Soundscape-COST, Oxford, 2013
- 662 [12] ISO 12913-1:2014, Acoustics - Soundscape - Part 1: Definition and conceptual framework.
- 663 [13] Drever J., *Sanitary Soundscapes: the noise effects from ultra-rapid ecological hand dryers on*
- 664 *vulnerable subgroups in publicly accessible toilets*, Proceedings of AIA-DAGA congress,
- 665 Meran (Italy) 18-21 march 2013
- 666 [14] Ortiz N. M., Schulte-Fortkamp B., *Quiet-zones, is “quiet” the correct identifier?*, Proceedings
- 667 of AIA-DAGA congress, Meran (Italy) 18-21 march 2013
- 668 [15] Lercher P., Eisenmann A., Dekoninck L., Botteldooren D., Widmann U., Evans G., *Noise*
- 669 *exposure and health effect in children: Results from a contextual soundscape perspective*,
- 670 Proceedings of AIA-DAGA congress, Meran (Italy) 18-21 March 2013
- 671 [16] Prodi N., Farnetani A., Visentin C., Fausti P., (2009), *Efficiency of communication in*
- 672 *auralized classrooms*. Proceedings of EURONOISE 2009, Edinburgh 26 – 28 October 2009,
- 673 ISBN 1901656985
- 674 [17] Hiramatsu K., *Soundscape concept in association with noise control*, in J. Kang K.
- 675 Chourmouziadou, K. Sakantamis, B. Wang, Y. Hao (edited by), *Soundscape of European*
- 676 *Cities and Landscape*, Soundscape-COST, Oxfors, 2013 pp.128-131
- 677 [18] Ordonez R., Visentin C., Markovic M., Fausti P., “Objective and subjective evaluation of
- 678 façade sound insulation”, Proceedings of INTERNOISE 2013 Noise Control for Quality of
- 679 Life, Innsbruck 15 – 18 September 2013, ISBN 978-16-32662-67-5
- 680 [19] Bettarello F., Fausti P., Baccan V. and Caniato M., “Impact Sound Pressure Level
- 681 Performances of Basic Beam Floor Structures”, Journal of Building Acoustics, Volume 17,
- 682 No.4, 2010, pp. 305-316, ISSN 1351-010X, DOI 10.1260/1351-010X.17.4.305.
- 683 [20] Caniato M., Bettarello F., Marsich L., Ferluga A., Sbaizero O., Schmid C., Time-depending
- 62
- 63
- 64
- 65



684 performance of resilient layers under floating floors, *Construction and Building Materials*  
685 102, 226-232131.

686 [21] Di Bella A., Fausti P., Scamoni F., Secchi S., Italian experiences on acoustic classification of  
687 buildings, *Proceedings of Inter Noise 2012*, New York, USA, August 19-22, 2012, ISSN  
688 0736-2935.

689 [22] Cremonini R., Fausti P., “Considerations on low frequencies results of in situ sound insulation  
690 measurements”, *Proceedings of AIA-DAGA 2013 Conference*, Merano, Italy (2013), ISBN  
691 978-3-939296-05-8.

692 [23] World Health Organisation, (1999), ‘Guidelines for Community Noise’, World Health  
693 Organisation, Geneva

694 [24] National Italian Law D.P.C.M. 14-11-97, *Determination of the limit values of noise sources*,  
695 G.U. n. 280, 1-12-97.

696 [25] Roberts C., *Ecoaccess guideline for assessment of low frequency noise*, ” in *Proceedings of*  
697 *ACOUSTICS 2004*, Gold Coast, Australia, November 2004

698 [26] DIN 45680 – *Measurement and evaluation of low-frequency noise immissions in the*  
699 *neighbourhood*, 1997

700 [27] Draft DIN 45680, *Measurement and evaluation of low-frequency noise immissions*, 2013

701 [28] EN 60651– *Specification for sound level meters*, 1994

702 [29] ISO 226 – *Acoustics – Normal equal-loudness-level contours*, 2003

703 [30] Broner N. J., *A simple criterion for low frequency noise emission assessment*, *Journal of Low*  
704 *Frequency Noise, Vibration and Active Control*, Vol. 29, No. 1 (2010), pp 1-13

705 [31] Caniato M., Bettarello F., Taffarel M., *Sound power level of speaking people*, *Proceedings of*  
706 *Meetings on Acoustics*, Volume 19, 2013, Article number 040026

707 [32] M. Caniato, F. Bettarello, F. Patrizio, L. Marsich, A. Ferluga, C. Schmid, *Low frequency*  
708 *noise and assessment methods: A brief literature overview*, 22st International Congress on  
709 Acoustics, ICA 2016

710  
711  
712  
713  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65